Product: Epigen Chemproof 4029TC "B" Page 1 of 6 Date of Issue: January 2021

H	azardous according to criteria of Worksafe Australia	
1 PRODUCT & COMPANY UN	NDERTAKING IDENTIFICATION	
Product Name:	EPIGEN CHEMPROOF 4029TC "B"	
Product Code:	4029TCB	
Major Recommended Use:	High build coating when mixed with "A".	
Company:	Peerless Industrial Systems Pty Ltd	
ABN:	14 097 615 391	
Address:	PO Box 407 Cloverdale WA 6985 AUSTRALIA	
Telephone Number:	61 (08) 9477 3788	
Fax Number:	61 (08) 9477 3766	
Email:	service@peerlessindustrialsystems.com	
Emergency Telephone Number:	13 11 26	
2 HAZARDS IDENTIFICATIO	Ν	
	4	
Acute Toxicity - Oral, Category 4 Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms:		
Sensitisation – Skin, Category 1A GHS Label Element		
Sensitisation – Skin, Category 1A GHS Label Element		
Sensitisation – Skin, Category 1A GHS Label Element		
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms:	DANGER	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word:	Image: White State Stat	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word:	Image: White State Stat	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word:	Image: Wight of the system DANGER H302 Harmful if swallowed H312 Harmful in contact with skin. H315 Causes skin irritation	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word:	Image: Wight of the system Im	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word:	Image: Way of the system of	
Sensitisation – Skin, Category 1A GHS Label Element	Image: Wight of the system Im	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word: Hazard statements:	Image: Non-StressImage: Non-StressANGERH302 Harmful if swallowedH302 Harmful in contact with skin.H315 Causes skin irritationH315 Causes skin irritationH317 May cause allergic skin reaction.H318 Causes serious eye damage.H412 Harmful to aquatic life with long lasting effects	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word: Hazard statements:	Image: Non-StressImage: Non-StressDANGERImage: Non-StressH302 Harmful if swallowedImage: Non-StressH312 Harmful in contact with skin.Image: Non-StressH315 Causes skin irritationImage: Non-StressH315 Causes skin irritationImage: Non-StressH317 May cause allergic skin reaction.Image: Non-StressH318 Causes serious eye damage.Image: Non-StressH412 Harmful to aquatic life with long lasting effectsP102 Keep out of reach of children	
Sensitisation – Skin, Category 1A GHS Label Element Hazard pictograms: Signal Word:	Image: Non-StressImage: Non-StressANGERH302 Harmful if swallowedH302 Harmful in contact with skin.H315 Causes skin irritationH315 Causes skin irritationH317 May cause allergic skin reaction.H318 Causes serious eye damage.H412 Harmful to aquatic life with long lasting effects	

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear eye/face protection, gloves, protective clothing.

Response statements:

P101 If medical advice is needed, have product container or label at hand
P301+P330+P331 IF SWALLOWED: rinse mouth. DO NOT induce vomiting
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated
clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several
minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a
position comfortable for breathing
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P391 Collect spillage.

P501 Dispose of contents/ container to an approved waste disposal plant.

Product: Epigen Chemproof 4029TC "B" Page 2 of 6 Date of Issue: January 2021

Poison Schedule (Australia) S5

Other hazards which do not result in classification None known.

3 COMPOSITION/INFORMATION ON INGREDIENTS			
Chemical Name	CAS Number	Proportion	
Phenolic-Fromaldehyde Resin	9003-35-4	<40%	
3 Aminomethyl 3,5,5 Trimethylcyclohexylamine	2855-13-2	<20%	
Cycloaliphatic Amine	Trade Secret	<10%	
Ingredients determined not to be hazardous	not applicable	to 100%	

4 FIRST AID MEASURES

General advice:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
lf inhaled:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed:	Clean mouth with water and drink afterwards plenty of water. DO NOT induce vomiting and call a physician. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms: and effects, both acute and delayed.	irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation May cause allergic skin reaction Causes serious eye irritation
Notes to physician:	Treat symptomatically.

5 FIRE FIGHTING MEASURES

Suitable extinguishing media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific hazards during fire fighting:	Sudden reaction and fire may result if product is mixed with an oxidising agent. Incomplete combustion may form carbon monoxide. May generate ammonia gas. May generate toxic nitrogen oxide gases.

Product: Epigen Chemproof 4029TC "B" Page 3 of 6 Date of Issue: January 2021

Hazardous combustion: products:	May generate toxic, irritating or flammable combustion products.
	Collect contaminated fire extinguishing water separately. This must not be discharged to drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment:	In the event of fire, wear self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

7 HANDLING & STORAGE

Advice on protection against fire and explosion:	Normal measures for preventive fire protection.
Advice on safe handling:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which a mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Hygiene measures:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of the workday.
Conditions for safe storage:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

SAFETY DATA SHEET Product: Epigen Chemproof 4029TC "B" Page 4 of 6 Date of Issue: January 2021

Hand protection:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates it is necessary.
Eye protection:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific workplace.

9 PHYSICAL & CHEMICAL PROPERTIES

Appearance: Colour: Odour: Odour Threshold: pH: Melting Point: Boiling Point (@760mm Hg): Flashpoint (°C): Evaporation rate: Flammability: Upper explosion limit: Lower explosion limit: Lower explosion limit: Vapour Pressure (mm Hg): Relative Vapour Density: Density: Solubility in Water: Partition Coefficient n-Octanol/Water Auto-ignition temperature:	Thick Liquid Pale Opaque None discernible Not available Not available Not available Not available > 200°C Closed Cup No data available Not applicable Not available Not available Not available Not available 1.35 Insoluble Not available Not available
Partition Coefficient n-Octanol/Water	Not available
U	
Decomposition temperature:	Not available
Per cent Volatiles:	< 0.5%
Volatile Organic Compounds:	< 0.5%

10 STABILITY & REACTIVITY

Reactivity:	No dangerous reaction known under conditions of normal use.
Chemical stability:	The product is chemically stable.
Possibility of hazardous reactions:	Stable under recommended storage conditions.
Conditions to avoid:	Heat and sources of ignition.
Incompatible materials:	Strong oxidizing materials.

11 TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects:

Skin contact : Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic skin reaction.

Eye contact: Causes serious eye irritation. Category

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract

Product: Epigen Chemproof 4029TC "B" Page 5 of 6 Date of Issue: January 2021

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Acute toxicity: Not classified based on available information.

Chronic toxicity:

Germ cell mutagenicity:	Not classified based on available information.
Carcinogenicity:	Not classified based on available information.
Reproductive toxicity:	Not classified based on available information.
STOT – single exposure:	Not classified based on available information.
STOT – repeated exposure:	Not classified based on available information.
Aspiration toxicity:	Not classified based on available information.

Information specifically related to Isophoronediamine

TOXICITY

Oral (rat) LD50: 1030 mg/kg

12 ECOLOGICAL INFORMATION		
Ecotoxicity:	No data available.	
Persistence and degradability:	No data available.	
Bioaccumulative potential:	No data available.	
Mobility in soil:	No data available.	

Other adverse effects

Product:

Additional ecological information: Avoid contaminating waterways or discharging to sewers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS	
Disposal methods Waste from residues:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

14 TRANSPORT INFORMATION

International Regulation

IATA-DGR

UN/ID No. Proper Shipping Name: 3,5,5 Trimethylcyclohexylamine). Class: UN 2735 Amines, liquid, corrosive, n.o.s.(contains Cycloaliphatic Amine, 3 Aminomethyl

8 Corrosive

SAFETY DATA SHEET Product: Epigen Chemproof 4029TC "B" Page 6 of 6 Date of Issue: January 2021

Packing group: Labels: Packing instruction (cargo aircraft): Packing instruction (passenger aircraft):	III 8 856 852
IMDG-Code UN number: Proper shipping name: 3,5,5 Trimethylcyclohexylamine). Class: Packing group: Labels: EmS Code: Marine pollutant:	UN 2735 Amines, liquid, corrosive, n.o.s.(contains Cycloaliphatic Amine, 3 Aminomethyl 8 Corrosive III 8 F-A, S-B Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Road & Rail Transport"Australian Code for the Transport of Dangerous Goods by Road & Rail"UN number:UN 2735Proper shipping name:Amines, liquid, corrosive, n.o.s.(contains Cycloaliphatic Amine, 3 Aminomethyl3,5,5 Trimethylcyclohexylamine).8 CorrosiveClass:8 CorrosivePacking group:IIILabels:8

15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture.

Standard for the Uniform Scheduling Schedule 5 of Medicines and Poisons:

International Chemical Weapons Convention (CWC) Not applicable Schedules of Toxic Chemicals and Precursors

Prohibition / Licensing Requirements: There is no applicable prohibition or notification / licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

On the inventory, or in compliance with the inventory.

16 OTHER INFORMATION

Date format: January 2021

AICS:

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: <u>www.epigen.com.au</u>

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material